

# All stainless steel process gauge open or solid front

## Model T5500 and T6500

According EN 837-1  
 Nominal size 100 mm or 160 mm  
 Accuracy: Class 1 (DIN)



### Features

- Rugged stainless steel construction
- Socket and case welded
- Protection IP54 and IP65
- Optional ATEX approved  $\text{CE} \text{ (Ex)} \text{ II 2 GD c}$
- Usable to full scale
- Overload protection 130 %
- Dry, liquid filled or liquid less (*PLUS!* gauge)
- Measuring system stainless steel or Monel
- Optional contacts

### Ranges

-1 ... 0 bar up to 0 ... 2500 bar  
 -30 in. Hg ... 0 psi up to 0 ... 36.000 psi

### Applications

Chemical and petrochemical industry  
 Machine and apparatus construction  
 Food and beverage industry  
 Pulp and paper industry

Technical specification	T5500		T6500	
	100	160	100	160
Dial size [mm]	100	160	100	160
Construction	Open front cylindrical case with blow out disc at the back		Solid front safety pattern cylindrical case with blow out at the back	
Measuring principle	Bourdon tube			
Range [bar]	0,6 1 1,6 2,5 4 6 10 16 25 40 60 100 160 250 400 600 1000			
Overpressure limit	130 % F.S., short time			
Pressure type	Gauge, vacuum and compound			
Process connection	G 1/4 B male, G 1/2 B male, G 3/8 B male according EN 837, M20x1,5 male, R 1/2 male tapered (DIN 2999), 1/2" male straight (JIS, BSP), 3/8" male straight (JIS, BSP), 1/4 NPT male, 1/2 NPT male according ANSI/ASME B1.20.1, 9/16-18 UNF-2B Aminco (high pressure), Others on request (for pressure limitations see order information)			
Connection location	Lower, back		Lower only	
Material	Stainless steel 316L (1.4404), optional Monel			
Pressure connection	Stainless steel 316L (1.4404), optional Monel, > 1000 bar Ni Span			
Tube	Stainless steel 304 (1.4301), optional 316L (1.4404)			
Case/bayonet ring	Instrument glass, optional laminated safety glass or Laminated safety glass, optional acrylic glass			
Window	acrylic glass			
Dial	Aluminum, black markings on white background			
Pointer	Aluminum, black, optional micrometer adjustment, red set hand or maximum pointer			
Movement	Stainless steel 304/303 (1.4301/1.4305)			
Accuracy	Class 1 (1 % F.S.), optional 0,5 % F.S.			
Permissible	-25 ... 60 °C			
Ambient temperature	Max. 200 °C (dry), max. 100 °C (liquid filled)			
Medium temperature	-40 ... 60 °C			
Storage temperature	Max. 0,3 % / 10 K			
Effect				
Protection according EN 60 529/IEC 529	IP54 (dry), IP65 (liquid filled), optional IP65 for dry gauges			
Conformity according to RL 94/9/EC appendix X for mechanical equipment in potential hazardous areas	Optional, Marking $\text{CE} \text{ (Ex)} \text{ II 2 GD c}$ File no. 800314628 at notified body 0032, TÜV NORD CERT (only with safety glass and protection IP65 or liquid filling)		T4 (T <sub>amb</sub> -20 ... 60 °C, T <sub>med</sub> -20 ... 100 °C) T5 (T <sub>amb</sub> -20 ... 60 °C, T <sub>med</sub> -20 ... 70 °C) T6 (T <sub>amb</sub> -20 ... 60 °C, T <sub>med</sub> -20 ... 55 °C)	
Filling liquids	Glycerin, silicone, halocarbon, others on request Optional dampened movement (liquid less gauge), functions as liquid filled gauge ( <i>PLUS!</i> gauge)			
Mounting	Standard stem, optional flush or surface, others on request			
Weight dry/filled [kg]	0,8/1,0	1,2/2,0	0,8/1,0	1,2/2,0
Accessories, options	Diaphragm seals, valves, gauges with contacts (see G1.K55/E), gauges with electrical output, NACE			